

				
<b>Model</b>	<b>GDS3710</b>	<b>2N Helios IP Force</b>	<b>Mobotix T25</b>	<b>Fanvil i31</b>
<b>Lens Type</b>	180° x 150°	135° x 109°	180° x 160°	120°
<b>PoE</b>	Yes	Yes	Yes, optional	Yes
<b>SIP/VoIP Support</b>	Yes, broad interoperability	Yes	Yes	Yes, broad interoperability
<b>Voice Codecs</b>	G.711μ/a-law, G.722	G.711, G.729, G.722, L16/16kHz	G.711u/a-law	G.711a/u, G.722, G.723.1, G.726-32K, G.729AB, iLBC, AMR
<b>Video Codecs</b>	H.264 High Profile, Motion JPEG	H.264, H.263, H.263+, Motion JPEG	H.264 for SIP, Motion JPEG	H.264, Motion JPEG
<b>Video Resolution</b>	1920 x 1080p	1280 x 960p	2048 x 1536p	1280 x 720p
<b>Max Frame Rate</b>	30fps	30fps	30fps	30fps
<b>Simultaneous Tri-stream Video</b>	Yes, 1080p for NVR, 720p for video phones/computers, 320p for mobile phone	No	No	No
<b>RFID</b>	Yes	Yes, optional	Yes, optional	Yes
<b>Built-in Key Pad</b>	Yes, capacitive touch keys	Yes, optional, mechanical keys	Yes, optional, mechanical keys	Yes, mechanical keys
<b>Audio Input</b>	Integrated microphone (AEC with excellent background noise suppression)	2 integrated microphones (AEC)	Integrated microphone	Integrated microphone
<b>Audio Output</b>	HD loudspeaker up to 3m	Loudspeaker up to 1 m	Loudspeaker	Loudspeaker
<b>Day &amp; Night Mode</b>	Yes, white LEDs for face-brightening	Yes, infrared light	Yes, optional	Yes, infrared light

				
<b>Model</b>	<b>GDS3710</b>	<b>2N Helios IP Force</b>	<b>Mobotix T25</b>	<b>Fanvil i31</b>
<b>No. of Alarm In &amp; Out</b>	2 channels	Yes, optional	Yes, optional	2 channels
<b>Waterproof Cert.</b>	IP66	IP65	IP65	IP65
<b>Vandal Resistance</b>	IK09	IK10	N/A	IK10
<b>Mounting</b>	Wall Surface, In Wall (Flushing)	Wall Surface, In Wall (Flushing)	In Wall (Flushing)	Wall Surface, In Wall (Flushing)
<b>Temperature Range</b>	-30°C to 60°C	-40 to 55 °C	-30 to 50°C	-40 to 70°C